

Variant table BMR350

Part Number	V _{in} Range	V _{out} Setpoint	V _{out} Range	I _{out} TDP	P _{out} TDP	P _{out} Peak	Parallel-able	Digital Header	Digital Pinout	Baseplate Type	Other features
BMR350x320/802	40-60V	12.12V	8-13.2V	50A	600W	N/A	No	7-pin	PG/CTRL; S-; SDA; SALERT; SCL; SA1; S+	Flat baseplate	Sense pin
BMR350x102/002	40-60V	12.2V	8-13.2V	72A	860W	N/A	Yes - DLS	7-pin	PG; DGND; SDA; SALERT; SCL; SA1; SA0	Flat baseplate	
BMR350x101/801	40-60V	12.12V	8-13.2V	72A	860W	N/A	Yes - ACS	7-pin	S+; S-; SDA; SALERT; SCL; SA1; IMON	Open deck baseplate	Sense pin
BMR350x100/031	40-60V	12V	8-13.2V	72A	860W	1200W	Yes - ACS	7-pin	PG; DGND; SDA; SALERT; SCL; SA1; IMON	Open deck baseplate	
BMR350x253/803	40-60V	12.2V	8-13.2V	108A	1300W	1700W	Yes - DLS	7-pin	PG; S-; SDA; SALERT; SCL; SA1; S+	Open deck baseplate	Sense pin
BMR350x250/531	40-60V	12.12V	8-13.2V	108A	1300W	N/A	Yes - ACS	7-pin	PG; DGND; SDA; SALERT; SCL; SA1; IMON	Open deck baseplate	

X = pin length option ("0" = 5.33mm ; "2" = 3.69mm; "3" = 4.57mm; "4" = 2.79mm)