


IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)
CB SCHEME

CB TEST CERTIFICATE

Product	Dual output POL
Name and address of the applicant	Flex Electronics (Shanghai) Co Ltd 33 Fuhua Road, Jiading District Shanghai, 201818 China
Name and address of the manufacturer	Flex Electronics (Shanghai) Co Ltd 33 Fuhua Road, Jiading District Shanghai, 201818 China
Name and address of the factory <small>Note: When more than one factory, please report on page 2</small>	Flex Electronics (Shanghai) Co., Ltd 33 Fuhua Road, Jiading District Shanghai, 201818 China <input type="checkbox"/> Additional Information on page 2
Ratings and principal characteristics	See Page 2
Trademark (if any)	
Type of Customer's Testing Facility (CTF) Stage used	
Model / Type Ref.	BMR 469X1X2X3X4/X5X6X7, BMR 469 0000/001 See Page 2
Additional information (if necessary may also be reported on page 2)	The report was revised to include technical modifications. <input checked="" type="checkbox"/> Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 62368-1:2014
As shown in the Test Report Ref. No. which forms part of this Certificate	OFF-4788220803-A-1-Amendment-1 issued on 2019-04-04

This CB Test Certificate is issued by the National Certification Body



- UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnamesDate: 2019-04-04
Original Issue Date: 2018-02-06

Signature:

Jan-Erik Storgaard

Model Details:

BMR 469X1X2X3X4/X5X6X7 (See Test Report - General Product Information for additional explanation)

Ratings:

(optional)

For Model BMR 469 0000/001

Input: 7.5--14Vdc, Max.33A;

For Two single-phase outputs:

Iout = 40 A (at Vout = 0.6 V)

Iout = 40 A (at Vout = 1.0 V)

Iout = 35 A (at Vout = 1.8 V)

Iout = 32.5 A (at Vout = 2.5 V)

Iout = 30 A (at Vout = 3.3 V)

Iout = 20 A (at Vout = 5.0 V)

For One dual-phase output:

Iout = 80 A (at Vout = 0.6 V)

Iout = 80 A (at Vout = 1.0 V)

Iout = 70 A (at Vout = 1.8 V)

Iout = 65 A (at Vout = 2.5 V)

Iout = 60 A (at Vout = 3.3 V)

Iout = 40 A (at Vout = 5.0 V)

For Model BMR 469X1X2X3X4/X5X6X7

Input: 7.5--14Vdc, Max.33A;

For Two single-phase outputs:

Iout = 50 A (at Vout = 0.6~5V)

For One dual-phase output:

Iout = 25 A (at Vout = 0.6 V~5V)

Additional Information:

Additionally evaluated to EN 62368-1:2014 /A11:2017; National Differences specified in the CB Test Report.

The original report was modified to include the following changes/additions:

- Add model number BMR 469X1X2X3X4/X5X6X7.
- Delete checked for Class III in Class of equipment.

Additional information (if necessary)



UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/names

Date: 2019-04-04

Original Issue Date: 2018-02-06

Signature:

Jan-Erik Storgaard