

DK-140761-A1-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Name and address of the applicant

Name and address of the manufacturer

Name and address of the factory

Note: When more than one factory, please report on page 2

Ratings and principal characteristics

Trademark / Brand (if any)

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

Additional information (if necessary may also be reported on page 2)

A sample of the product was tested and found to be in conformity with

As shown in the Test Report Ref. No. which forms part of this Certificate

DC-DC Converter

FLEX ELECTRONICS (SHANGHAI) CO LTD 33 FUHUA ROAD, JIADING DISTRICT SHANGHAI 201818 **CHINA**

Flex Electronics (Shanghai) Co Ltd 33 Fuhua Road, Jiading District Shanghai 201818 **CHINA**

Flex Electronics (Shanghai) Co Ltd 33 Fuhua Road, Jiading District Shanghai 201818 **CHINA**

☐ Additional Information on page 2

(optional) For model BMR684

Input: 34.5-60Vdc or 36-75Vdc, 22A; Output: 50Vdc, 14A, 700W



CTF Stage 2

BMR684X1X2X3X4/X5X6X7

□ Additional Information on page 2

Additionally evaluated to: EN 62368-1:2014, EN 62368-1:2014/A11:2017. The report was revised to include administrative modifications.

National Differences: EU Group Differences, CA, US

□ Additional Information on page 2

IEC 62368-1:2014

E496569-A6044-CB-1 issued on 2024-01-04

This CB Test Certificate is issued by the National Certification Body



□ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA

☑ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
☐ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Signature:

Thomas Wilson

Date: 2024-01-05

Original Issue Date: 2023-05-11



DK-140761-A1-UL

Additional Model Detail(s):

BMR684X1X2X3X4/X5X6X7,

X1 defines the Mechanical pin option

X1=1: TH - lead length 5.33 mm

X1=2: LA = lead length 3.69 mm

X1=3: LB = lead length 4.57 mm

X1=4: LC = lead length 2.79 mm

X1=5-9: TBD

X2 defines the Mechanical option

X2=0: Standard open frame

X2=1: Base plate

X2=2-9: TBD

X3X4 is used as sequence number for additional variants

X3X4=00: Vout 50V, 36-75Vin, 700W, DOSA 7 pin digital interface

X5X6X7 is used as sequence number for CDA files: Model number is CDA1020684/X5X6X7

X5X6X7 can be a number between 000 and 999. Both general numbers specified in the datasheet and customer unique numbers exists. All CDA sequence number are SW unique

Summary of Modifications:

- Delete one factory.

Additional information (if necessary)



☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA ☑ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

□ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN □ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

The I Wil

For full legal entity names see www.ul.com/ncbnames

Date: 2024-01-05

Original Issue Date: 2023-05-11

Signature:

Thomas Wilson