



Ref. Certif. No.

DK-140761-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	DC-DC Converter
Name and address of the applicant	Flex Electronics (Shanghai) Co Ltd 33 Fuhua Road, Jiading District Shanghai 201818 China
Name and address of the manufacturer	Flex Electronics (Shanghai) Co Ltd 33 Fuhua Road, Jiading District Shanghai 201818 China
Name and address of the factory	Flex Electronics (Shanghai) Co Ltd 33 Fuhua Road, Jiading District Shanghai 201818 China
Note: When more than one factory, please report on page 2	<input checked="" type="checkbox"/> Additional Information on page 2
Ratings and principal characteristics	(optional) For model BMR684 Input: 34.5-60Vdc or 36-75Vdc, 22A. Output: 50Vdc, 14A, 700W <input type="checkbox"/> Additional Information on page 2
Trademark / Brand (if any)	
Customer's Testing Facility (CTF) Stage used	CTF Stage 2
Model / Type Ref.	BMR684X1X2X3X4/X5X6X7 <input checked="" type="checkbox"/> Additional Information on page 2
Additional information (if necessary may also be reported on page 2)	Additionally evaluated to: EN 62368-1:2014, EN 62368-1:2014/A11:2017 National Difference specified in the CB Test Report. <input type="checkbox"/> Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 62368-1:2014
As shown in the Test Report Ref. No. which forms part of this Certificate	E496569-A6044-CB-1 issued on 2023-05-11

This CB Test Certificate is issued by the National Certification Body



- UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2023-05-11

Signature: Thomas Wilson



Ref. Certif. No.

DK-140761-UL

Factory(ies):

FLEXTRONICS TECHNOLOGY (PENANG) SDN BHD
BUKIT MINYAK INDUSTRIAL PARK S P T
PLOT 131A JALAN PERINDUSTRIAN BUKIT
BUKIT MINYAK SIMPANG AMPAT, PULAU PINANG, 14100
Malaysia

Additional Model Detail(s):

BMR684X1X2X3X4/X5X6X7,
X1 defines the Mechanical pin option
X1=1: TH - lead length 5.33 mm
X1=2: LA = lead length 3.69 mm
X1=3: LB = lead length 4.57 mm
X1=4: LC = lead length 2.79 mm
X1=5-9: TBD
X2 defines the Mechanical option
X2=0: Standard open frame
X2=1: Base plate
X2=2-9: TBD
X3X4 is used as sequence number for additional variants
X3X4=00: Vout 50V, 36-75Vin, 700W, DOSA 7 pin digital interface
X3X4=01-99: TBD
X5X6X7 is used as sequence number for CDA files: Model number is CDA1020684/X5X6X7
X5X6X7 can be a number between 000 and 999. Both general numbers specified in the datasheet and customer unique numbers exists. All CDA sequence number are SW unique.

Additional information (if necessary)



- UL Solutions (US), 333 Pflingsten Rd IL 60062, Northbrook, USA
- UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2023-05-11

Signature:

Thomas Wilson