Certificate Number UL-US-2336901-0

Report Reference E496569-20230830

Date 5-Sep-2023

Issued to: Flex Electronics (Shanghai) Co Ltd

33 Fuhua Road, Jiading District Shanghai, Shanghai Shi 201818

China

This is to certify that representative samples of

QQJQ2 - Power Supplies for Use with Audio/Video, Information and Communication Technology Equipment -

Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in

in certain constructional features or restricted in

performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: UL 62368-1, 2nd Ed., Issue Date: 2014-12-01

Additional Information: See the UL Online Certifications Directory at

https://iq.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.

Deborah Jennings-Conner, VP Regulatory Services



Certificate Number UL-US-2336901-0 Report Reference E496569-20230830

Date 5-Sep-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
BMR320X1X2X3X4/X5X6X7, X1 defines the Mechanical	DC-DC Converter
pin option	
X1=0: TH - Standard Pin length	
X1=1: SMD, box pins, Module height 6.4mm	
X1=2-9: TBD	
X2 defines the Mechanical option	
X2=0: Open frame	
X2=1-9: TBD	
X3X4 is used as sequence number for additional	
variants	
X3X4=00: First 8:1 trafo variant, 40-60Vin, Vout 6.75Vo.	
(Trafo 8:1)	
X3X4=01-99: TBD	
X5X6X7 is used as sequence number for CDA files	
Model number is CDA102 0320/ X5X6X7	
X5X6X7 can be a number between 001 and 999. Both	
general numbers specified in the datasheet and	
starting from /001.	
customer unique numbers exist. All CDA sequence number are SW unique. Standard CDA should be used, starting from /001.	

Debrah Jenning - Course

Deborah Jennings-Conner, VP Regulatory Services



 Certificate Number
 UL-CA-2331830-0

 Report Reference
 E496569-20230830

Date 5-Sep-2023

Issued to: Flex Electronics (Shanghai) Co Ltd

33 Fuhua Road, Jiading District Shanghai, Shanghai Shi 201818

China

This is to certify that representative samples of

QQJQ8 - Power Supplies for Use with Audio/Video, Information and Communication Technology Equipment

Certified for Canada - Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional factures or restricted in

in certain constructional features or restricted in

performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: CSA C22.2 No. 62368-1-14, 2nd Ed., Issue Date: 2014-12-

01

Additional Information: See the UL Online Certifications Directory at

https://ig.ulprospector.com for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.

Deborah Jennings-Conner, VP Regulatory Services

Olbrah Jennings-Course





 Certificate Number
 UL-CA-2331830-0

 Report Reference
 E496569-20230830

Date 5-Sep-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
BMR320X1X2X3X4/X5X6X7, X1 defines the Mechanical	DC-DC Converter
pin option	
X1=0: TH - Standard Pin length	
X1=1: SMD, box pins, Module height 6.4mm	
X1=2-9: TBD	
X2 defines the Mechanical option	
X2=0: Open frame	
X2=1-9: TBD	
X3X4 is used as sequence number for additional	
variants	
X3X4=00: First 8:1 trafo variant, 40-60Vin, Vout 6.75Vo.	
(Trafo 8:1)	
X3X4=01-99: TBD	
X5X6X7 is used as sequence number for CDA files	
Model number is CDA102 0320/ X5X6X7	
X5X6X7 can be a number between 001 and 999. Both	
general numbers specified in the datasheet and	
customer unique numbers exist. All CDA sequence	
number are SW unique. Standard CDA should be used,	
starting from /001.	

Olbrah Jennings-Course

Deborah Jennings-Conner, VP Regulatory Services

